

6016KBTF19MVN Quick coupling with hose barb

Quick coupling double shut-off, hose barb 19mm (3/4), nominal diameter 16, <20 bar, brass nickel plated, seal FKM





Kein Foto vorhanden

Product description

This range of couplings was constructed with valves as an alternative to the French profiles. All four nominal diameters in our Frenchmatic I range are available with single and double shut-off.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Connection	Hose barb 19mm LW(3/4")
Connection description	Hose barb 19mm LW(3/4")
Connection type	Hose barb
Suitable breath / respiratory protection	No
Seal	FKM
Seal description	Fluororubber
Working pressure	PB = 20 bar, maximum static working pressure with safety factor of 4 to 1.
Pressure eliminator	No
Single-hand operation	Yes
Self-venting coupling	No
Flat-sealing	No
Mould coupling	Yes
Weight in kg	0,001
Hydraulics	No
Ball locking	Yes
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm ²	200
Bore in mm	16
Surface	nickel plated
Pneumatics	No
Professional recommendation	Cooling Injection Moulds
Series	6016
Series long	6016KB
Safety locking system	No
Standard product	No
Pin lock	No
Working temperature	-15°C up to +200°C (FKM) depending on the medium
Ultra-FLO-valve	No
Vacuum suitable	Yes
Advantages	The locking balls guarantee an optimum hold by the insert connection even with forces acting from the side. Optimum flow rate with absolute minimal flow resistance.
Water-resistant	Yes
Material connection	Brass nickel plated
Material seal	Viton®
Material sleeve	Brass nickel plated
Material spring snap ring	stainless steel AISI 301
Material balls/pins	Stainless steel AISI 420
Material valve	Brass
Material valve body	Brass nickel plated
Two-hand operation	No

Dimensions

Connection A	19 mm
D mm	38
L mm	112,5
L1 mm	36