

## 2KRAW13IW13 Swivel joint


Swivel joint female-/male thread G 1/4 auf G 1/4, max. 350 bar



### Product description

Can be used in hydraulic systems where rotating connections are essential, for example on accessories with rotating movements. Depending on design, the body is made of brass (DG) or steel (KR) and the rotating axis of surfacepurified/stainless steel. Maximum rotation speed: 60 r.p.m.

### More images



#### Product properties

|                                 |                                                                                                                                                                                                                              |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection type                 | Female / Male thread                                                                                                                                                                                                         |
| Seal                            | NBR                                                                                                                                                                                                                          |
| Weight in kg                    | 0,272                                                                                                                                                                                                                        |
| Hydraulics                      | Yes                                                                                                                                                                                                                          |
| Maximum working pressure in bar | 350                                                                                                                                                                                                                          |
| Professional recommendation     | Hydraulics                                                                                                                                                                                                                   |
| Series                          | KR                                                                                                                                                                                                                           |
| Series long                     | KR                                                                                                                                                                                                                           |
| Working temperature             | -40°C up to +90°C (NBR) depending on the medium.                                                                                                                                                                             |
| Advantages                      | Rotating joints minimise the high wear to the hose, which occurs in hydraulic systems. Solid construction with two plain bearings (DG) or ball/ roller bearings (KR). Suitable for combining with norm hydraulic components. |
| Material axis of rotation       | Steel hardened, zinc-plated, passivated, sealed                                                                                                                                                                              |
| Material counterpart            | Steel, zinc-plated, passivated, sealed                                                                                                                                                                                       |
| Material body                   | Steel, zinc-plated, passivated, sealed                                                                                                                                                                                       |
| Material nut/adapter            | Steel, zinc-plated, passivated, sealed                                                                                                                                                                                       |
| Additional information          | only suitable for oil                                                                                                                                                                                                        |

#### Dimensions

|               |        |
|---------------|--------|
| Connection A  | G 1/4" |
| Connection A1 | G 1/4" |
| D mm          | 29     |
| L mm          | 88     |
| SW mm         | 27     |
| SW1 mm        | 19     |