

3KRAW17IW17 Swivel joint


Swivel joint female-/male thread G 3/8 auf G 3/8, max. 350 bar



Product description

Can be used in hydraulic systems where rotating connections are essential, for example on accessories with rotating movements. Depending on design, the body is made of brass (DG) or steel (KR) and the rotating axis of surfacepurified/stainless steel. Maximum rotation speed: 60 r.p.m.

More images



Product properties

Connection type	Female / Male thread
Seal	NBR
Weight in kg	0,316
Hydraulics	Yes
Maximum working pressure in bar	350
Professional recommendation	Hydraulics
Series	KR
Series long	KR
Working temperature	-40°C up to +90°C (NBR) depending on the medium.
Advantages	Rotating joints minimise the high wear to the hose, which occurs in hydraulic systems. Solid construction with two plain bearings (DG) or ball/ roller bearings (KR). Suitable for combining with norm hydraulic components.
Material axis of rotation	Steel hardened, zinc-plated, passivated, sealed
Material counterpart	Steel, zinc-plated, passivated, sealed
Material body	Steel, zinc-plated, passivated, sealed
Material nut/adapter	Steel, zinc-plated, passivated, sealed
Additional information	only suitable for oil

Dimensions

Connection A	G 3/8"
Connection A1	G 3/8"
D mm	33
L mm	87
SW mm	30
SW1 mm	22