

## ET13/06FX Threaded nozzle with bulkhead fitting


Threaded nozzle with bulkhead fitting, PVDF, G 1/4, 6 mm



### Product description

Threaded nozzle with bulkhead fitting - PVDF - G 1/4, 6 mm

### More images



**Product properties**

|                            |                    |
|----------------------------|--------------------|
| <b>Working pressure</b>    | 0 up to 8 bar      |
| <b>Weight in kg</b>        | 0,0053             |
| <b>Material</b>            | PVDF               |
| <b>Working temperature</b> | -20°C up to +120°C |

**Dimensions**

|                      |                    |
|----------------------|--------------------|
| <b>Connection 1</b>  | Male thread G 1/4" |
| <b>Connection 2</b>  | Hose tail 6 mm     |
| <b>Connection A</b>  | G 1/4              |
| <b>Connection A1</b> | 6 mm               |
| <b>B mm</b>          | 4                  |
| <b>G mm</b>          | M 12x1             |
| <b>L mm</b>          | 43                 |
| <b>L1 mm</b>         | 8                  |
| <b>L2 mm</b>         | 8                  |
| <b>L3 mm</b>         | 14                 |
| <b>SW mm</b>         | 14                 |
| <b>SW1 mm</b>        | 17                 |