

5020 RUV Hydraulic plug




Hydraulic plug straight-through, female thread G 1/2, nominal diameter 13, 300 bar, stainless steel AISI 316 L



Product description

The TEMA Standard Series is characterised by a low pressure drop and maximum flow capacity. The coupling system is available as double shut-off or straight through version. The 2500 can be used also as a single shut-off version.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Female thread 1/2"
Connection type	Female thread
Coupled working pressure in bar	300
Pressure eliminator	No
Single-hand operation	Yes
Flat-sealing	No
Weight in kg	0,083
Size in general	1/2"
Hydraulics	Yes
Ball locking	Yes
Material	stainless steel AISI 316 L
Bore area in mm ²	133
Bore in mm	13
Professional recommendation	Hydraulics
Series	T
Series long	5000
Safety locking system	No
Working temperature	-30°C up to +100°C (NBR) -25°C up to +200°C (FKM) depending on the medium.
Vacuum suitable	No
Valve	without
Advantages	Hoher Durchfluss – minimaler Druckabfall. Doppelte Sicherheit durch doppelte O-Ring-Abdichtung. Sicherheits-Schließring verhindert ungewolltes Entkuppeln. Korrosionsbeständig. Kleine Dimensionen.
Material spring snap ring	1.4310
Material valve body	1.4404
Two-hand operation	No

Dimensions

Connection A	G 1/2"
D mm	30
L mm	42
SW mm	27