

6603-12-12 Hydraulikschnellkupplung




0



Product description

Die Serie IA7500 ist nach den Vorschriften und Maßen der Normspezifikationen ISO 7241-1, Serie A hergestellt.

More images



Product properties

Shut-off	Quick coupling Double Shut-Off
Old order number	IA7510
Connection	Female thread 3/4"
Connection type	Female thread
Coupled working pressure in bar	280
Seal	NBR
Pressure eliminator	No
Single-hand operation	Yes
Flat-sealing	No
Weight in kg	0,64
Size in general	3/4"
Hydraulics	Yes
Ball locking	Yes
Material	Steel
Bore area in mm ²	314
Bore in mm	20
Professional recommendation	Hydraulics
Series	IA
Series long	6600 (IA7500)
Safety locking system	No
Working temperature	-30°C up to +100°C (NBR) depending on the medium.
Vacuum suitable	No
Valve	with
Advantages	NBR seals and back-up ring in PTFE to withstand flow surges at high flow rates. Single acting sleeve. Poppet valving. Chrome 6 freeplated steel.
Material sleeve	Steel
Material spring snap ring	Stainless steel
Material balls/pins	Steel
Material valve	Steel
Material valve holder	Stainless steel
Material valve body	Steel
Two-hand operation	No

Dimensions

Connection A	G 3/4"
D mm	47,6
L mm	85,5
SW mm	41