

## Spring balancer 77001300


Spring balancer, payload range 0 - 0,5 kg, cable length 1,6 m, easy load setting



### Product description

Spring balancer for lightweight and hand-operated tools that have to be kept ready in a predetermined position. High stability and quality. The casing is made of extremely shockproof special plastic, red-orange. The cable drum is made of abrasion-resistant plastic. High-strength steel cable with elastic cable stop buffer and lightweight carabiner for hanging the load. High-strength special mainspring. Easy load setting protected against operating error. Load mounting with secure carabiner. Hanging with screwing carabiner. Longer cables available on demand.

### More images



Product properties

|                            |                                                  |
|----------------------------|--------------------------------------------------|
| Fall protection            | Existing, according to DIN 15112                 |
| Locking                    | No                                               |
| Suspension                 | Screwing carabiner                               |
| Spring fracture protection | No                                               |
| Weight in kg               | 0,4                                              |
| Material casing            | Shockproof special plastic                       |
| Cable stop                 | Yes, shock absorbing and adjustable              |
| Series                     | 7200                                             |
| Series long                | 7200                                             |
| Load attachment            | Carabiner                                        |
| Payload range in kg        | 0 - 0,5                                          |
| Load setting               | Easy setting - protected against operating error |

Dimensions

|                   |     |
|-------------------|-----|
| Cable length in m | 1,6 |
|-------------------|-----|