

## Spring balancer 77001403


Spring balancer, payload range 7 - 10 kg, cable length 3 m, infinitely variable load setting



### Product description

Spring balancers for continuous operation with smooth withdrawal. The 3,0 meters cable length is well suitable for the rough requirements in daily use. The hanging is done through a freely turnable and traversable screwing carabiner. The casing is made of shockproof and abrasion-resistant plastic, red-orange. The blockable cable drum is made of abrasion-resistant plastic. Infinitely variable load setting through adjusting screw with over-twist protection. Load mounting with screwing carabiner. The cable stop buffer is shockproof and adjustable. The cable length is infinitely variable adjustable through a cable lock. High-strength and bandaged special mainspring. Longer cables available on demand.

### More images



Product properties

|                            |                                                    |
|----------------------------|----------------------------------------------------|
| Fall protection            | Existing, according to DIN 15112                   |
| Locking                    | No                                                 |
| Suspension                 | Freely turnable and traversable screwing carabiner |
| Spring fracture protection | Yes                                                |
| Weight in kg               | 3,7                                                |
| Material casing            | Shockproof special plastic                         |
| Cable stop                 | Yes, shock absorbing and adjustable                |
| Series                     | 7221                                               |
| Series long                | 7221                                               |
| Load attachment            | Screwing carabiner                                 |
| Payload range in kg        | 7 - 10                                             |
| Load setting               | Through adjusting screw with over-twist protection |

Dimensions

|                   |   |
|-------------------|---|
| Cable length in m | 3 |
|-------------------|---|