

Spring balancer 77001411


Spring balancer, payload range 2 - 5 kg, cable length 3 m, infinitely variable load setting, automatic locking



Product description

Spring balancers for continuous operation with smooth withdrawal. The 3,0 meters cable length is well suitable for the rough requirements in daily use. The hanging is done through a freely turnable and traversable screwing carabiner. The casing is made of shockproof and abrasion-resistant plastic, red-orange. The blockable cable drum is made of abrasion-resistant plastic. Infinitely variable load setting through adjusting screw with over-twist protection. Load mounting with screwing carabiner. The cable stop buffer is shockproof and adjustable. The cable length is infinitely variable adjustable through a cable lock. High-strength and bandaged special mainspring. The automatic locking of the cable windup makes it possible to block the device. Longer cables available on demand.

More images



Product properties

Fall protection	Existing, according to DIN 15112
Locking	Yes
Suspension	Freely turnable and traversable screwing carabiner
Spring fracture protection	Yes
Weight in kg	3,5
Material casing	Shockproof special plastic
Cable stop	Yes, shock absorbing and adjustable
Series	7222
Series long	7222
Load attachment	Screwing carabiner
Payload range in kg	2 - 5
Load setting	Through adjusting screw with over-twist protection
Additional information	Do not use the locking for changing the load!

Dimensions

Cable length in m	3
-------------------	---