

Hose balancer 77000652


Hose balancer, payload range 1,2 - 2,2 kg, cable length 0,8 m, with quick coupling and hose tail 6 mm, air connection R 1/4"i.



Product description

Hose balancer for industrial applications. Hanging with a turnable screwing carabiner. Casing and cable drum are made of shockproof and abrasion-resistant plastic, red-orange. Casing lid made of sheet steel, painted. High-strength and sturdy (damage-resistant) air hose with inner width of 6 mm and attached quick coupling. Air supply through R1/4" female thread on the casing. The working stroke can be infinitely variable shortened. High-strength riveted special mainspring. Longer hose available on demand. The hose stop buffer is infinitely variable adjustable. Maximum working pressure: 10 bar Air passage: 860 l/min at 6 bar.

More images



Product properties

Fall protection	Existing, according to DIN 15112
Connection (casing)	Female thread R 1/4"
Connection (hose)	Quick coupling and plug 6 mm
Locking	No
Suspension	Turnable and traversable screwing carabiner
Spring fracture protection	No
Weight in kg	1,3
Material casing	Shockproof and abrasion-resistant plastic
Maximum working pressure in bar	10
max. inlet pressure	10
Cable stop	Yes, shock absorbing and adjustable
Series	7223
Series long	7223
Payload range in kg	1,2 - 2,2
Load setting	by screening mit Allen key
Additional information	Air flow rate is identical in withdrawn and extended state of the hose.

Dimensions

Hose Inner diameter in mm	6
Cable length in m	0,8