

## 3109 10 21 Stud elbow


LF 3000 standard pneumatic, stud elbow, Engineered polymer, 10 mm - R1/2



### Product description

Connection of tubing at 90° with a male thread. Tightened on the top of the fitting with a flat spanner or Allen key to facilitate assembly in tight spaces. Solid construction, aesthetic and unobtrusive for a better connection. Precoated thread ensuring direct sealing and full air flow. Individual unit quality control and dating in order to guarantee quality and traceability. Complies RoHS and ISO 14743.

### More images



#### Product properties

|                                        |                     |
|----------------------------------------|---------------------|
| <b>Special feature</b>                 | schwenkbar          |
| <b>Seal coating</b>                    | PTFE                |
| <b>Weight in kg</b>                    | 0,03                |
| <b>Maximum working pressure in bar</b> | 20                  |
| <b>max. temperature in °C</b>          | 80                  |
| <b>min. temperature in °C</b>          | -20                 |
| <b>RoHS compliant</b>                  | Yes                 |
| <b>Vacuum resistance in mm Hg</b>      | 755                 |
| <b>Material seal</b>                   | NBR                 |
| <b>Material body</b>                   | Engineered polymer  |
| <b>Material threaded fitting</b>       | Brass nickel plated |
| <b>Material toothed washer</b>         | Stainless steel     |

#### Dimensions

|           |       |
|-----------|-------|
| <b>C</b>  | R1/2" |
| <b>F</b>  | 21    |
| <b>G</b>  | 16    |
| <b>H</b>  | 22    |
| <b>L</b>  | 26,5  |
| <b>ØD</b> | 10 mm |