

## 3183 04 06 L-connection


LF 3000 standard pneumatic, L-connection, Engineered polymer, 2 x 4 mm - 6 mm



### Product description

In line connection of 2 tubes at a 90° angle with another push-in fitting or cartridge. compact.solid construction, aesthetic and unobtrusive for a better connection. Full air flow. Individual unit quality control and dating in order to guarantee quality and traceability. Complies RoHS and ISO 14743.

### More images



**Product properties**

|                                        |                    |
|----------------------------------------|--------------------|
| <b>Weight in kg</b>                    | 0,007              |
| <b>Maximum working pressure in bar</b> | 20                 |
| <b>max. temperature in °C</b>          | 80                 |
| <b>min. temperature in °C</b>          | -20                |
| <b>RoHS compliant</b>                  | Yes                |
| <b>Vacuum resistance in mm Hg</b>      | 755                |
| <b>Material seal</b>                   | NBR                |
| <b>Material body</b>                   | Engineered polymer |
| <b>Material toothed washer</b>         | Stainless steel    |

**Dimensions**

|            |      |
|------------|------|
| <b>G</b>   | 10,5 |
| <b>H</b>   | 38,5 |
| <b>H1</b>  | 7    |
| <b>H2</b>  | 17   |
| <b>L</b>   | 17,5 |
| <b>ØD1</b> | 4 mm |
| <b>ØD2</b> | 6 mm |