

## 3089 10 10 Elbow connection

Carstick cartridges, Polymere-cartridge Quick-Fitting - Elbow connection, Engineered polymer, 10 mm




### Product description

Connection of tubing at a 90° angle to a customised assembly with cavities prepared for the insertion of cartridges.

- Easier installation of components and assemblies.
- No thread to machining in your housing.
- Possibility of having different tube diameters for only one cavity diameter.
- Individual unit quality control and dating in order to guarantee quality and traceability.
- Vacuum capability
- ROHS.

### More images



## Product properties

|                                 |                     |
|---------------------------------|---------------------|
| Weight in kg                    | 0,017               |
| Maximum working pressure in bar | 20                  |
| max. temperature in °C          | 80                  |
| min. temperature in °C          | -20                 |
| RoHS compliant                  | Yes                 |
| Vacuum resistance in mm Hg      | 755                 |
| Material seal                   | NBR                 |
| Material body                   | Engineered polymer  |
| Material threaded fitting       | Brass nickel plated |
| Material toothed washer         | Stainless steel     |

## Dimensions

|                 |       |
|-----------------|-------|
| Bohrung Ø in mm | 10    |
| G               | 16    |
| G1              | 19    |
| H               | 19    |
| L               | 26,5  |
| ØD              | 10 mm |