

## 3299 03 19 Compact stud elbow


LF 3200 - Miniature-pneumatics, Compact stud elbow, Brass nickel plated, 3 mm - M5x0,8



### Product description

Connection of tubing at a 90° angle with a male thread. solid construction, aesthetic and unobtrusive for a better connection. Full air flow. Individual unit quality control and dating in order to guarantee quality and traceability. Complies RoHS and ISO 14743.

### More images



**Product properties**

|                                 |                     |
|---------------------------------|---------------------|
| Weight in kg                    | 0,005               |
| Maximum working pressure in bar | 18                  |
| max. temperature in °C          | 70                  |
| min. temperature in °C          | -15                 |
| RoHS compliant                  | Yes                 |
| Material seal ring              | PTFE                |
| Material seal                   | NBR                 |
| Material body                   | Brass nickel plated |
| Material threaded fitting       | Brass nickel plated |
| Material release button         | Brass nickel plated |

**Dimensions**

|           |        |
|-----------|--------|
| <b>C</b>  | M5x0,8 |
| <b>F</b>  | 8      |
| <b>G</b>  | 6      |
| <b>H</b>  | 13     |
| <b>J</b>  | 6      |
| <b>L</b>  | 13,5   |
| <b>ØD</b> | 3 mm   |