

## 3675 08 17 Male stud coupling


LF 3600 - Brass special - Industrie and food, male stud coupling, Brass nickel plated chemical fda brass, 8 mm - R3/8



### Product description

In-line connection of tubing to a threaded port. External tightening with a flat spanner or a socket wrench, internal adjustment with an Allen key. Solid construction and compact design. Excellent resistance to corrosion. Individual unit quality control and dating in order to guarantee quality and traceability. Components meet FDA standard and 1935/2004/EC regulation and comply RoHS.

### More images



Product properties

|                                 |                                        |
|---------------------------------|----------------------------------------|
| Weight in kg                    | 0,027                                  |
| Maximum working pressure in bar | 30                                     |
| max. temperature in °C          | 150                                    |
| min. temperature in °C          | -20                                    |
| RoHS compliant                  | Yes                                    |
| Vacuum resistance in mm Hg      | 755                                    |
| Material seal ring              | Brass nickel plated chemical fda brass |
| Material seal                   | FKM                                    |
| Material body                   | Brass nickel plated chemical fda brass |
| Material release button         | Brass nickel plated chemical fda brass |

Dimensions

|           |       |
|-----------|-------|
| <b>C</b>  | R3/8" |
| <b>F1</b> | 17    |
| <b>F2</b> | 6     |
| <b>H</b>  | 18,5  |
| <b>ØD</b> | 8 mm  |