

## 3699 04 19 Compact stud elbow


LF 3600 - Brass special - Industrie and food, Compact stud elbow, Brass nickel plated  
chemical fda brass, 4 mm - M5x0,8



### Product description

Connection of tubing at a 90° angle to a threaded port. Solid construction and compact design. Excellent resistance to corrosion. Individual unit quality control and dating in order to guarantee quality and traceability. Components meet FDA standard and 1935/2004/EC regulation and comply RoHS.

### More images



#### Product properties

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| <b>Special feature</b>                 | schwenkbar                             |
| <b>Weight in kg</b>                    | 0,011                                  |
| <b>Maximum working pressure in bar</b> | 20                                     |
| <b>max. temperature in °C</b>          | 150                                    |
| <b>min. temperature in °C</b>          | -20                                    |
| <b>RoHS compliant</b>                  | Yes                                    |
| <b>Vacuum resistance in mm Hg</b>      | 755                                    |
| <b>Material seal ring</b>              | Brass nickel plated chemical fda brass |
| <b>Material seal</b>                   | FKM                                    |
| <b>Material body</b>                   | Brass nickel plated chemical fda brass |
| <b>Material threaded fitting</b>       | Brass nickel plated chemical fda brass |
| <b>Material release button</b>         | Brass nickel plated chemical fda brass |

#### Dimensions

|           |        |
|-----------|--------|
| <b>C</b>  | M5x0,8 |
| <b>E</b>  | 3,5    |
| <b>F</b>  | 10     |
| <b>G</b>  | 10     |
| <b>H</b>  | 18     |
| <b>J</b>  | 7      |
| <b>L</b>  | 18     |
| <b>ØD</b> | 4 mm   |