

## 3803 10 17 L-stud coupling

LF 3800 / LF 3900 - Stainless steel, L-stud coupling, Stainless steel 316l, 2 x 10 mm - R3/8




### Product description

In line connection of 2 tubes at a 90° angle to a threaded port.

- materials: Stainless steel, sealings: FKM
- stainless steel components and FKM seals for use in aggressive environments
- strong construction and compact
- hygienic design aimed at reducing retention zones for safe and easy cleaning ( $R_a < 0,8$  surface)
- permitting permanent contact with foodstuffs
- individual unit quality control and dating in order to guarantee quality and traceability
- materials conforming to FDA and 1934/2004 CE standards

### More images



**Product properties**

|                                 |                      |
|---------------------------------|----------------------|
| Weight in kg                    | 0,084                |
| Maximum working pressure in bar | 30                   |
| max. temperature in °C          | 120                  |
| min. temperature in °C          | -20                  |
| RoHS compliant                  | Yes                  |
| Material seal ring              | Stainless steel 316l |
| Material seal                   | FKM                  |
| Material body                   | Stainless steel 316l |
| Material threaded fitting       | Stainless steel 316l |
| Material release button         | Stainless steel 303  |

**Dimensions**

|           |       |
|-----------|-------|
| <b>C</b>  | R3/8" |
| <b>F</b>  | 19    |
| <b>G</b>  | 17,5  |
| <b>H</b>  | 30    |
| <b>H1</b> | 29    |
| <b>L</b>  | 38    |
| <b>ØD</b> | 10 mm |