

## 3805 10 17 Male stud coupling

LF 3800 / LF 3900 - Stainless steel, male stud coupling, Stainless steel 316l, 10 mm - R3/8




### Product description

male stud coupling. External tightening with a flat spanner or socket wrench, internal adjustment with an Allen key.

- materials: Stainless steel, sealings: FKM
- stainless steel components and FKM seals for use in aggressive environments
- strong construction and compact
- hygienic design aimed at reducing retention zones for safe and easy cleaning ( $R_a < 0,8$  surface)
- permitting permanent contact with foodstuffs
- individual unit quality control and dating in order to guarantee quality and traceability
- materials conforming to FDA and 1934/2004 CE standards

### More images



**Product properties**

|                                        |                      |
|----------------------------------------|----------------------|
| <b>Weight in kg</b>                    | 0,03                 |
| <b>Maximum working pressure in bar</b> | 30                   |
| <b>max. temperature in °C</b>          | 120                  |
| <b>min. temperature in °C</b>          | -20                  |
| <b>RoHS compliant</b>                  | Yes                  |
| <b>Material seal ring</b>              | Stainless steel 316l |
| <b>Material seal</b>                   | FKM                  |
| <b>Material body</b>                   | Stainless steel 316l |
| <b>Material release button</b>         | Stainless steel 303  |

**Dimensions**

|           |       |
|-----------|-------|
| <b>C</b>  | R3/8" |
| <b>F</b>  | 19    |
| <b>F1</b> | 6     |
| <b>H</b>  | 22,5  |
| <b>ØD</b> | 10 mm |