

## 0414 06 08 Ball valve

Ball valves Brass, 2/2-way ball valve with compression fitting, Brass nickel plated, NW 6, for tube 8 mm




### Product description

In-line ball valve for closing fluid systems with a simple quarter turn of the handle.

- suitable for use with steel tube
- full flow
- optimum sealing due to compensating O rings
- excellent resistance to scaling due to ball seal configuration.

### More images



**Product properties**

|                                        |                            |
|----------------------------------------|----------------------------|
| <b>Weight in kg</b>                    | 0,18                       |
| <b>Maximum working pressure in bar</b> | 40                         |
| <b>max. temperature in °C</b>          | 80                         |
| <b>min. temperature in °C</b>          | -40                        |
| <b>Bore in mm</b>                      | 6                          |
| <b>RoHS compliant</b>                  | Yes                        |
| <b>Material seal</b>                   | NBR                        |
| <b>Material body</b>                   | Brass nickel plated        |
| <b>Material gripping ring</b>          | Brass                      |
| <b>Material seat seal</b>              | NBR                        |
| <b>Material lever</b>                  | Zamac                      |
| <b>Material stem</b>                   | Brass, Brass nickel plated |
| <b>Material plug sockets O-ring</b>    | NBR                        |
| <b>Material union nut</b>              | Brass nickel plated        |

**Dimensions**

|           |      |
|-----------|------|
| <b>F</b>  | 14   |
| <b>F1</b> | 19   |
| <b>H</b>  | 38   |
| <b>H1</b> | 31   |
| <b>J</b>  | 19   |
| <b>L</b>  | 74   |
| <b>L1</b> | 30   |
| <b>M</b>  | 48   |
| <b>ØD</b> | 8 mm |