

## 0461 12 21 Ball valve

Ball valves Brass, 3/2-way ball valve with threaded exhaust, Brass nickel plated, NW 12, G1/2




### Product description

With vent. For full or partial venting of the pipes. Single flow direction (signed with an arrow on the body).

- full flow
- optimum sealing due to compensating O rings
- excellent resistance to scaling due to ball seal configuration.

### More images



## Product properties

|                                 |                            |
|---------------------------------|----------------------------|
| Weight in kg                    | 0,304                      |
| Maximum working pressure in bar | 20                         |
| max. temperature in °C          | 80                         |
| min. temperature in °C          | -40                        |
| Bore in mm                      | 12                         |
| RoHS compliant                  | Yes                        |
| Material seal                   | NBR                        |
| Material body                   | Brass nickel plated        |
| Material seat seal              | NBR                        |
| Material lever                  | Zamac                      |
| Material stem                   | Brass, Brass nickel plated |
| Material plug sockets O-ring    | NBR                        |

## Dimensions

|    |       |
|----|-------|
| C  | G1/2" |
| E  | 15    |
| E1 | 12    |
| F  | 27    |
| H  | 47    |
| H1 | 44    |
| H2 | 33    |
| J  | 29    |
| L  | 49    |
| L1 | 34    |
| M  | 69    |