

## 0483 23 34 Ball valve

Ball valves Brass, 3/3-way T-ball valve not lockable, Brass nickel plated, NW 23, G1




### Product description

Female threaded with T-bore and closed position. For opening and closing a fluid system with a simple half turn of the handle.

- suitable for use with steel tube
- full flow
- optimum sealing due to compensating O rings
- excellent resistance to scaling due to ball seal configuration.

### More images



## Product properties

|                                 |                            |
|---------------------------------|----------------------------|
| Weight in kg                    | 1,066                      |
| Maximum working pressure in bar | 20                         |
| max. temperature in °C          | 80                         |
| min. temperature in °C          | -40                        |
| Bore in mm                      | 23                         |
| RoHS compliant                  | Yes                        |
| Material seal                   | NBR                        |
| Material body                   | Brass nickel plated        |
| Material seat seal              | NBR                        |
| Material lever                  | Zamac                      |
| Material stem                   | Brass, Brass nickel plated |
| Material plug sockets O-ring    | NBR                        |

## Dimensions

|    |     |
|----|-----|
| C  | G1" |
| E  | 19  |
| F  | 46  |
| H  | 63  |
| H1 | 55  |
| H2 | 47  |
| J  | 48  |
| L  | 94  |
| L1 | 47  |
| M  | 108 |