

## 0489 10 17 Ball valve

Ball valves Brass, 3/2-way ball valve with threaded exhaust, Brass nickel plated, NW 10, G3/8




### Product description

In-line vented. For full or partial venting of the pipes. Single flow direction (signed with an arrow on the body).

- full flow
- optimum sealing due to compensating O rings
- excellent resistance to scaling due to ball seal configuration.

### More images



**Product properties**

|                                        |                            |
|----------------------------------------|----------------------------|
| <b>Weight in kg</b>                    | 0,243                      |
| <b>Maximum working pressure in bar</b> | 40                         |
| <b>max. temperature in °C</b>          | 80                         |
| <b>min. temperature in °C</b>          | -40                        |
| <b>Bore in mm</b>                      | 10                         |
| <b>RoHS compliant</b>                  | Yes                        |
| <b>Material seal</b>                   | NBR                        |
| <b>Material body</b>                   | Brass nickel plated        |
| <b>Material seat seal</b>              | NBR                        |
| <b>Material lever</b>                  | Zamac                      |
| <b>Material stem</b>                   | Brass, Brass nickel plated |
| <b>Material plug sockets O-ring</b>    | NBR                        |

**Dimensions**

|           |        |
|-----------|--------|
| <b>C</b>  | G3/8"  |
| <b>C1</b> | M5x0,8 |
| <b>E</b>  | 12     |
| <b>F</b>  | 24     |
| <b>F1</b> | 24     |
| <b>H</b>  | 46     |
| <b>H1</b> | 43     |
| <b>H2</b> | 17     |
| <b>L</b>  | 59     |
| <b>L1</b> | 31     |
| <b>M</b>  | 69     |
| <b>T</b>  | 2      |