

## 7828 00 10 Sensor fitting

Sensor fittings, Pneumatic / electric sensor fittings, G1/8




### Product description

sensor fittings, electric signal output:

- G-thread or metric thread, NPT-thread or UNF-thread
- Recognize and signalize pressure drop: easy to use due to their low exhaust back pressure
- supplied with 3 core 0.5 mm<sup>2</sup> cable, length 2 metres
- compact, perfectly suited to your installations
- with pneumatic or electronic signal, they can be assembled on the cylinder or control valve

### More images



**Product properties**

|                                        |                    |
|----------------------------------------|--------------------|
| <b>Weight in kg</b>                    | 0,138              |
| <b>Maximum working pressure in bar</b> | 8                  |
| <b>max. temperature in °C</b>          | 60                 |
| <b>min. temperature in °C</b>          | -15                |
| <b>RoHS compliant</b>                  | Yes                |
| <b>Material seal ring</b>              | Engineered polymer |
| <b>Material seal</b>                   | NBR                |
| <b>Material adjusting spindle</b>      | Brass              |
| <b>Material body</b>                   | Engineered polymer |

**Dimensions**

|           |       |
|-----------|-------|
| <b>C</b>  | G1/8" |
| <b>F</b>  | 6     |
| <b>H</b>  | 20    |
| <b>H1</b> | 10    |
| <b>J</b>  | 16    |
| <b>L</b>  | 52    |
| <b>L1</b> | 8     |