

Filter/regulator/lubricator (three-part) Newdeal - 1224054


Three-part service unit Newdeal, connection G 1/4", flow rate 140 l/min., degree of filtration 20 µm, maximum inlet pressure 18 bar



Product description

Robust service unit made of metal.
Adjusted pressure stays constant despite pressure variations.
Metal container with 360° viewing window.
Quantity of lubricant proportioned to air flow.
Micrometric regulation of lubricant flow.
Activates at low flow rates.
Including pressure gauge.

More images



Product properties

Shielding	Technopolymer
Shielding plate	Technopolymer
Connection	Female thread G 1/4"
Type of oiling	Drip lubricator
Container	Aluminium
Seals	NBR
Dome	Technopolymer
Flow rate in l/min	140
Adjustment spring	Steel
Adjustment knob	Technopolymer
Adjusting nut	Brass Ms58
Adjusting screw	Brass Ms58
Filter element	HDPE
Filterfeinheit in µm	20
Weight in kg	0,945
Inner container	Transparent technopolymer
Piston	Technopolymer
Body	Zamac
Lip seal	NBR
max. inlet pressure	18
Oil sight glass	Technopolymer
Control needle	Brass Ms58
Ring nut	Technopolymer
Hose	Rislan®
Series	Newdeal
Bar	Brass Ms58
Plug	Technopolymer
Valve spring	Steel
Valve part	Vulcanized with NBR
Venturi system	NBR
Centrifuge	Technopolymer

Dimensions

A	42
B	190
D	126
E	116
G	20
L	M4 suitable
N	1/8" pressure gauge connection