

Regulator Syntesi - 5613R143

Regulator Syntesi, connection G 3/8", flow rate 3350 l/min., maximum inlet pressure 15 bar



Product description

Rolling diaphragm regulator.


Adjusted pressure stays constant despite pressure variations.

Padlockable push-lock knob.

Including pressure gauge.

Additional ports for pressure gauges, pressure switches or for use as additional air take-offs.

More images



Product properties

Connection	Female thread G 3/8"
Seals	NBR O-Ring
Flow rate in l/min	3350
Input and output socket	Brass Ms58 or aluminum, anodized
Adjustment spring	Steel
Adjustment knob	Technopolymer
Flange	Technopolymer
Weight in kg	0,174
Bell	Technopolymer
max. inlet pressure	15
Board	Technopolymer
Regulator case	Technopolymer
Regulator screw	Brass Ms58
Ring nut	Technopolymer
Series	Syntesi
Securing plate adjustment knob	Steel, zinc-plated
Tappet	Technopolymer
Valve	Messing Ms58 vulcanized with NBR
Valve spring	Stainless steel
Closure	Technopolymer

Dimensions

A1	44
B	102
C	44
D	51,5
E	33,5
F	25,8
G	Hole for screws M4
I	16
L	M30x1,5
M	1/8" (Pressure gauge connection or additional air intake)