

## MUB 23-70 Air motor


Air motor, reversible, speed under load 70 rpm, torque 32 Nm, holding load of brake 47 Nm



### Product description

The robustness distinguishes the air motor as unproblematic drive engine. It is well utilised in industrial sectors where accuracy and longevity are required. Its high starting torque and the wide torque range qualifies it for many needs in the drive section. The model **MUB 23** is equipped with a **brake actuated by force**. This brake is controlled directly with the ingoing air line. No further guiding hoses are necessary. The maximum brake force is equal to the starting torque. All data related to 6.3 bar working pressure.

### More images



Product properties

|                         |                 |
|-------------------------|-----------------|
| Resistant to stalling   | Yes             |
| Item number             | 60009107        |
| ATEX available          | Yes             |
| Brake                   | Yes             |
| Torque in Nm            | 32              |
| Maximum torque in Nm    | 63              |
| Direction of rotation   | Reversible      |
| Weight in kg            | 3,2             |
| Holding load of brake   | 47              |
| Torque in Nm            | 32              |
| Speed under load in rpm | 70              |
| Idling speed rpm        | 140             |
| Power in kW             | 0,23            |
| Air consumption in l/s  | 7,8             |
| Material                | Stainless steel |
| Non-lubricated          | Yes             |
| Start torque in Nm      | 47              |
| Shaft load Fa max. in N | 1800            |
| Shaft load Fr max. in N | 3900            |

Dimensions

|                           |   |
|---------------------------|---|
| Hose Inner diameter in mm | 8 |
|---------------------------|---|