

## MUD 40-2400 Air motor


Air motor, reversible, speed under load 2400 rpm, torque 2 Nm, start torque 3 Nm



## Product description

The robustness distinguishes the air motor as unproblematic drive engine. It is well utilised in industrial sectors where accuracy and longevity are required. Its high starting torque and the wide torque range qualifies it for many needs in the drive section. **Reversible motors** can be used rotating clockwise and anti clockwise. It is very important that if the air motor is pressurized with connection turning the air motor left, the connection turning the air motor right is vented properly (and vice versa). All data related to 6.3 bar working pressure.

### More images



Product properties

|                         |                 |
|-------------------------|-----------------|
| Resistant to stalling   | Yes             |
| Item number             | 60033197        |
| ATEX available          | Yes             |
| Brake                   | No              |
| Torque in Nm            | 2               |
| Maximum torque in Nm    | 4               |
| Direction of rotation   | Reversible      |
| Weight in kg            | 1,7             |
| Torque in Nm            | 2               |
| Speed under load in rpm | 2400            |
| Idling speed rpm        | 4800            |
| Power in kW             | 0,5             |
| Air consumption in l/s  | 12,6            |
| Material                | Stainless steel |
| Non-lubricated          | No              |
| Start torque in Nm      | 3               |
| Shaft load Fa max. in N | 1500            |
| Shaft load Fr max. in N | 2100            |

Dimensions

|                           |    |
|---------------------------|----|
| Hose Inner diameter in mm | 10 |
|---------------------------|----|