

WSE 34 NA WaterProfi-plug G 3/4" AG

WaterProfi-plug with male thread (valve adaptor) G 3/4" AG, stainless steel, DN 9




Product description

WaterProfi plugs **series WSE** are made of stainless steel which offers a more robust and wear resistance vs other couplings made of plastics. Furthermore the stainless steel couplings can be used in applications with special sanitation requirements or for hot water (e.g. for cleaning in food industry). The one-hand operation guarantees a simplified work and an optimum ease of use. WaterProfi products are outfitted with O-rings to offer best sealing characteristics. That means: leakages can be avoided with the coupling system as often seen with pre-mounted compression fittings now in the past.

The series WSE is also compatible with the plug profile usual for the market.

More images



Product properties

Shut-off	Plug Straight-Through
Connection	Male thread 3/4"
Suitable breath / respiratory protection	No
Seal	EPDM
Pressure eliminator	No
Single-hand operation	No
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,074
Hydraulics	No
Ball locking	No
Material	stainless steel AISI 303
Maximum working pressure in bar	PN 16 bar
max. temperature in °C	+95°C
Bore	DN 9
Pneumatics	No
Professional recommendation	Water
Series	WSE
Series long	WSE
Safety locking system	No
Standard product	No
Pin lock	No
Ultra-FLO-valve	No
Vacuum suitable	No
Water-resistant	No
Two-hand operation	No

Dimensions

B mm	32
L mm	41