

## 6814 10 17 Stud fitting

Stud fitting CleanFit®, Brass nickel plated chemical fda brass, 10 mm, G3/8"



### Product description

In line connection of tubing with a male thread. Tightened on the top of the fitting with a flat spanner or socket wrench

Robust eco-conception, aesthetic design and superior level of cleanliness for a perfect compatibility

Airtight, antistatic packaging


Full flow

100 % leak-tested, date coding to guarantee quality and traceability

ASTM G93-03 B 300, ISO 15001, VDI 2083

Conform to CGA G4.1 and DI93/42/EC

### More images



**Product properties**

|                                        |                                        |
|----------------------------------------|----------------------------------------|
| <b>Weight in kg</b>                    | 0,027                                  |
| <b>Material</b>                        | Brass nickel plated chemical fda brass |
| <b>Maximum working pressure in bar</b> | 15                                     |
| <b>max. temperature in °C</b>          | 95                                     |
| <b>min. temperature in °C</b>          | -10                                    |
| <b>RoHS compliant</b>                  | Yes                                    |
| <b>Vacuum resistance in mm Hg</b>      | 755                                    |
| <b>Material seal</b>                   | EPDM                                   |
| <b>Material body</b>                   | Brass nickel plated chemical fda brass |
| <b>Material toothed washer</b>         | Stainless steel                        |

**Dimensions**

|           |       |
|-----------|-------|
| <b>C</b>  | G3/8" |
| <b>E</b>  | 14    |
| <b>F</b>  | 19    |
| <b>H</b>  | 36    |
| <b>ØD</b> | 10 mm |