

## 6899 12 21 Stud elbow

Stud elbow CleanFit®, Biobased raw materials, 12 mm, G1/2"



### Product description

Connection of tubing at 90° with a male thread. Tightened on the top of the fitting with a flat spanner or socket wrench.

Robust eco-conception, aesthetic design and superior level of cleanliness for a perfect compatibility

Airtight, antistatic packaging


Full flow

100 % leak-tested, date coding to guarantee quality and traceability

ASTM G93-03 B 300, ISO 15001, VDI 2083

Conform to CGA G4.1 and DI93/42/EC

### More images



Product properties

|                                 |                                        |
|---------------------------------|----------------------------------------|
| Special feature                 | schwenkbar                             |
| Weight in kg                    | 0,029                                  |
| Material                        | Biobased raw materials                 |
| Maximum working pressure in bar | 15                                     |
| max. temperature in °C          | 95                                     |
| min. temperature in °C          | -10                                    |
| RoHS compliant                  | Yes                                    |
| Vacuum resistance in mm Hg      | 755                                    |
| Material seal                   | EPDM                                   |
| Material body                   | Biobased raw materials                 |
| Material threaded fitting       | Brass nickel plated chemical fda brass |
| Material toothed washer         | Stainless steel                        |

Dimensions

|    |       |
|----|-------|
| C  | G1/2" |
| E  | 7     |
| F  | 24    |
| G  | 19    |
| H  | 42    |
| L  | 40    |
| ØD | 12 mm |