

## 6866 08 12 Plug-in reducer


Plug-in reducer CleanFit®, Biobased raw materials, 8 mm, 12 mm



### Product description

In-line connection of tubing of smaller diameter with another push-in fitting  
Robust eco-conception, aesthetic design and superior level of cleanliness for a perfect compatibility  
Airtight, antistatic packaging  
Full flow  
100 % leak-tested, date coding to guarantee quality and traceability  
ASTM G93-03 B 300, ISO 15001, VDI 2083  
Conform to CGA G4.1 and DI93/42/EC

### More images



**Product properties**

|                                        |                        |
|----------------------------------------|------------------------|
| <b>Weight in kg</b>                    | 0,004                  |
| <b>Material</b>                        | Biobased raw materials |
| <b>Maximum working pressure in bar</b> | 15                     |
| <b>max. temperature in °C</b>          | 95                     |
| <b>min. temperature in °C</b>          | -10                    |
| <b>RoHS compliant</b>                  | Yes                    |
| <b>Vacuum resistance in mm Hg</b>      | 755                    |
| <b>Material seal</b>                   | EPDM                   |
| <b>Material body</b>                   | Biobased raw materials |
| <b>Material toothed washer</b>         | Stainless steel        |

**Dimensions**

|            |       |
|------------|-------|
| <b>G</b>   | 13,5  |
| <b>L</b>   | 48,5  |
| <b>L1</b>  | 24,5  |
| <b>ØD</b>  | 8 mm  |
| <b>ØD1</b> | 12 mm |