

W3606000002 – IN-LINE PROGRESSIVE STARTER VAP 1/4

Inline progressive starter, female thread 1/4", 1.500 NI/min flow rate, anodized aluminium



Product description


The in-line progressive starter is a valve that regulates the flow of air until the outlet pressure reaches a certain value, at which the valve opens and allows air to flow at full rate.

This valve can be used to control a group of valves or a single valve, or it can be mounted between another valve and an actuator.

The air that enters inlet 1 passes through a choke that has a knob adjustment to control the flow. The valve opens completely when the outlet pressure reaches about 60% of the inlet pressure.

If the air supply is switched off, the valve discharges air from outlet 2 to inlet 1.

More images



Product properties

Connection	Female thread 1/4"
Flow rate through flow regulator	max. 200 NI/min (at 6.3 bar)
Flow rate in l/min	1500 NI/min (at 6.3 bar, ?P=1 bar)
Mounting position	In any position
Function	2/2 NC
Weight in kg	0,09
Maximum working pressure in bar	10 bar
max. operating frequency	5 Hz
Medium suitability	Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous.
Maximum working pressure in bar	2 bar
Switching pressure	About 60% of inlet pressure
Screw size	Min. M4x25
Working temperature	-10 – +70 °C
Material body	Anodized aluminium

Dimensions

A	56
A1	50
B	20
C	30
Ch	8
D	4,5
E	10
F	G 1/4
F1	G 1/4
H	49-52
I	25,5
I1	18
I2	16
L	10
P	9
P1	9