

9068112 – IN-LINE PRESSURE INDICATOR thread-pipe 3/8-Ø8 red

Inline pressure indicator, thread-pipe, 3/8-Ø8, red, 2 – 10 bar




Product description

The LAM L pneumatic light indicator belongs to the LINE ON LINE® family, which means it can be connected to all the other components in series or in parallel.

Available in the version for pipe-pipe connection with two FOX push-in fittings, and in the version for thread-pipe connection with a brass nickelplated male thread and a push-in fitting.

When there is no pressure, the clear technopolymer bell looks empty. When there is pressure, a red signal appears. The clear bell can be cleaned using normal detergents or ethyl alcohol, as the technopolymer used is fully compatible.

More images



Product properties

Colour with pressure	red
Working pressure	2 – 10 bar
Flow rate in l/min	800 NI/min (at 6.3 bar, ?P=1 bar)
Recommended pipe	Rilsan PA 11 – Nylon 6 – Polyamide 12 – Polypropylene.
Weight in kg	0,066
Medium suitability	Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous.
Working temperature	-20 – +60 °C

Dimensions

A	72,2
A1	34,8
Connection 1	Male thread G 3/8
Connection 2	Push-in fitting 8 mm outside calibrated
B	41
C	18,7
Ch	17
Ch1	17
D	9,1
E	22
E1	13,8
E2	10,6
F	3/8
G	26
H	M15x1
I	18,7
I1	24
N	4,5
Ø	8
P	9