

## 9065711 – IN-LINE STOP VALVE thread-pipe 1/4-Ø8

Inline stop valve, thread-pipe, 1/4-Ø8, 10 bar



### Product description

The STP L stop valve belongs to the LINE ON LINE® family and can be connected in series or in parallel with the other products in the same family.

It is available in a version for pipe-pipe connection, which includes two push-in fittings, and a version for thread-pipe connection, which includes a nickel-plated brass male thread and a push-in fitting.


The stop valve is normally mounted on the inlet port of cylinders and allows the flow of air only in the presence of a pneumatic pilot. Cylinder movement ceases if there is a drop in pneumatic pilot pressure.

The compressed air port is a push-in fitting for Ø 4 pipe.

This stop valve is available in a unidirectional version, so the flow can be interrupted in one direction, but remains free in the other direction.

This valve can also be used as a unidirectional normally-closed 2/2 pneumatic control valve.

### More images



#### Product properties

|                                        |                                                      |
|----------------------------------------|------------------------------------------------------|
| <b>Recommended pipe</b>                | Rilsan PA 11 – Nylon 6 – Polyamid 12 – Polypropylen. |
| <b>Weight in kg</b>                    | 0,074                                                |
| <b>Maximum working pressure in bar</b> | 10 bar                                               |
| <b>Medium suitability</b>              | Lubricated or unlubricated filtered air.             |
| <b>Working temperature</b>             | -20 – +60 °C                                         |

#### Dimensions

|                     |                                         |
|---------------------|-----------------------------------------|
| <b>A</b>            | 70,6                                    |
| <b>A1</b>           | 34,2                                    |
| <b>Connection 1</b> | Male thread G 1/4                       |
| <b>Connection 2</b> | Push-in fitting 8 mm outside calibrated |
| <b>B</b>            | 49,7                                    |
| <b>C</b>            | 18,7                                    |
| <b>Ch</b>           | 17                                      |
| <b>Ch1</b>          | 14                                      |
| <b>D</b>            | 9,1                                     |
| <b>E</b>            | 18                                      |
| <b>E1</b>           | 13,8                                    |
| <b>F</b>            | 1/4                                     |
| <b>G</b>            | 26                                      |
| <b>H</b>            | M15x1                                   |
| <b>I</b>            | 18,7                                    |
| <b>I1</b>           | 24                                      |
| <b>N</b>            | 4                                       |
| <b>Ø</b>            | 8                                       |
| <b>P</b>            | 8                                       |