

## 9064110 – IN-LINE CHECK VALVE SERIES VNR L thread-pipe 1/8-Ø8


Inline check valves, thread-pipe, 1/8-Ø8, 0,5 – 12 bar, 480 NI/min flow rate



### Product description

The VNR L check valve belongs to the LINE ON LINE® family, which means it can be connected to all the other components in series or in parallel. Available in the version for pipe-pipe connection with two push-in fittings, and in the version for thread-pipe connection with a brass nickel-plated male thread and a push-in fitting. It is still the only check valve with holes for wall mounting

### More images



**Product properties**

|                            |                                                                                                 |
|----------------------------|-------------------------------------------------------------------------------------------------|
| <b>Working pressure</b>    | 0,5 – 12 bar                                                                                    |
| <b>Flow rate in l/min</b>  | 480 NI/min (at 6.3 bar, ?P=1 bar)                                                               |
| <b>Recommended pipe</b>    | Rilsan PA 11 – Nylon 6 – Polyamide 12 – Polypropylene.                                          |
| <b>Weight in kg</b>        | 0,044                                                                                           |
| <b>Medium suitability</b>  | Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous. |
| <b>Working temperature</b> | -20 – +60 °C                                                                                    |

**Dimensions**

|                     |                                         |
|---------------------|-----------------------------------------|
| <b>A</b>            | 66,2                                    |
| <b>A1</b>           | 31,8                                    |
| <b>Connection 1</b> | Male thread G 1/8                       |
| <b>Connection 2</b> | Push-in fitting 8 mm outside calibrated |
| <b>B</b>            | 25,5                                    |
| <b>C</b>            | 18,7                                    |
| <b>Ch1</b>          | 14                                      |
| <b>E</b>            | 15                                      |
| <b>E1</b>           | 13,8                                    |
| <b>F</b>            | 1/8                                     |
| <b>I</b>            | 18,7                                    |
| <b>I1</b>           | 24                                      |
| <b>Ø</b>            | 8                                       |
| <b>P</b>            | 6                                       |