

9064101 – IN-LINE CHECK VALVE SERIES VNR L thread-pipe M5-Ø4


Inline check valves, thread-pipe, M5-Ø4, 0,5 – 12 bar, 80 NI/min flow rate



Product description

The VNR L check valve belongs to the LINE ON LINE® family, which means it can be connected to all the other components in series or in parallel. Available in the version for pipe-pipe connection with two push-in fittings, and in the version for thread-pipe connection with a brass nickel-plated male thread and a push-in fitting. It is still the only check valve with holes for wall mounting

More images



Product properties

Working pressure	0,5 – 12 bar
Flow rate in l/min	80 NI/min (at 6.3 bar, ?P=1 bar)
Recommended pipe	Rilsan PA 11 – Nylon 6 – Polyamide 12 – Polypropylene.
Weight in kg	0,014
Medium suitability	Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous.
Working temperature	-20 – +60 °C

Dimensions

A	47,7
A1	22,7
Connection 1	Male thread M 5
Connection 2	Push-in fitting 4 mm outside calibrated
B	17,5
C	10,7
Ch1	9
E	9,9
E1	10
F	M5
I	12,8
I1	16
Ø	4
P	4