

9064211 – IN-LINE CHECK VALVE SERIES VNR L pipe-thread Ø8-1/4


Inline check valves, pipe-thread, Ø8-1/4, 0,5 – 12 bar, 480 NI/min flow rate



Product description

The VNR L check valve belongs to the LINE ON LINE® family, which means it can be connected to all the other components in series or in parallel. Available in the version for pipe-pipe connection with two push-in fittings, and in the version for thread-pipe connection with a brass nickel-plated male thread and a push-in fitting. It is still the only check valve with holes for wall mounting

More images



Product properties

Working pressure	0,5 – 12 bar
Flow rate in l/min	480 NI/min (at 6.3 bar, ?P=1 bar)
Recommended pipe	Rilsan PA 11 – Nylon 6 – Polyamide 12 – Polypropylene.
Weight in kg	0,049
Medium suitability	Filtered, lubricated or unlubricated, compressed air. Lubrication, if used, must be continuous.
Working temperature	-20 – +60 °C

Dimensions

A	70,6
A1	34,2
Connection 1	Push-in fitting 8 mm outside calibrated
Connection 2	Male thread G 1/4
B	25,5
C	18,7
Ch1	14
E	18
E1	13,8
F	1/4
I	18,7
I1	24
Ø	8
P	8