

231A0210 SaveAir pressure regulator

SaveAir pressure regulator, outlet pressure 1 bar, supply pressure max. 18 bar, female thread G 1/4, zinc






Product description

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 15 bar to 5 bar. The regulator is suited for basic pressure control only with an outlet pressure tolerance of approx. $\pm 10\% \times 2$. Non-relieving function, therefore not recommended for applications such as nailers.

Select the pressure regulator according to the desired outlet pressure. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

More images



Product properties

Connection	Female thread G 1/4
Connection description	Female thread G 1/4
Outlet pressure	1 bar
Seal description	Nitrite-butadiene rubber
Flow rate in l/min	400
Case	Zinc
Weight in kg	0,09
Hydraulics	No
Material	Zinc
max. inlet pressure	18 bar
Medium suitability	compressed air or non-corrosive gases
Surface	blank finish
Pneumatics	Yes
Relieving function	non-relieving
Series	231
Series long	231
Working temperature	0°C up to +60°C
Advantages	• Higher safety through lower pressure. Tools and equipment protected against pressure damages. • Cost reduction through substantially reduced air consumption. • Noise reducing for tools.
Water-resistant	No
Material connection	Zinc
Material seal	NBR

Dimensions

A mm	34
Connection A	G 1/4
B mm	52
SW mm	17