

## 239K0280 EcoReg pressure regulator

EcoReg in-line pressure regulator for drinking water, outlet pressure 8 bar, supply pressure max. 10 bar, female thread G 1/4, Grivory®





### Product description

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 10 bar to 5 bar. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

Regulator for drinking water conforms to the FDA, EU and DIN 50930-6, TÜV drinking water directives

### More images



#### Product properties

|                               |                                                                |
|-------------------------------|----------------------------------------------------------------|
| <b>Connection</b>             | Female thread G 1/4                                            |
| <b>Connection description</b> | Female thread G 1/4                                            |
| <b>Outlet pressure</b>        | 8 bar                                                          |
| <b>Seal description</b>       | Fluororubber                                                   |
| <b>Flow rate in l/min</b>     | 4                                                              |
| <b>Case</b>                   | Grivory®                                                       |
| <b>Weight in kg</b>           | 0,125                                                          |
| <b>Hydraulics</b>             | No                                                             |
| <b>Material</b>               | Grivory®                                                       |
| <b>max. inlet pressure</b>    | 10 bar                                                         |
| <b>Medium suitability</b>     | drinking water                                                 |
| <b>Surface</b>                | blank finish                                                   |
| <b>Pneumatics</b>             | No                                                             |
| <b>Series</b>                 | 239K                                                           |
| <b>Series long</b>            | 239K                                                           |
| <b>Working temperature</b>    | +4°C up to +60°C                                               |
| <b>Advantages</b>             | Applications such as drinking water, food and medical industry |
| <b>Water-resistant</b>        | Yes                                                            |
| <b>Material connection</b>    | Grivory®                                                       |
| <b>Material seal</b>          | FPM                                                            |

#### Dimensions

|                     |       |
|---------------------|-------|
| <b>A mm</b>         | 34    |
| <b>Connection A</b> | G 1/4 |
| <b>B mm</b>         | 52    |
| <b>SW mm</b>        | 17    |