

232A0280 ToolReg pressure regulator

ToolReg Regulator with relieving function, outlet pressure 8 bar, supply pressure max. 25 bar, female thread G 1/4, aluminium





Product description

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 15 bar to 6 bar. With an outlet pressure tolerance of only $\pm 10\%$ *2 it is especially suitable for nailing machines.

Select the pressure regulator according to the desired outlet pressure. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

More images



Product properties

Connection	Female thread G 1/4
Connection description	Female thread G 1/4
Outlet pressure	8 bar
Seal description	Nitrite-butadiene rubber
Flow rate in l/min	800
Weight in kg	0,045
Hydraulics	No
Material	Aluminium
max. inlet pressure	25 bar
Medium suitability	compressed air or non-corrosive gases
Surface	blank finish
Pneumatics	Yes
Series	232
Series long	232
Working temperature	0°C up to +80°C
Advantages	• Higher safety through lower pressure. Tools and equipment protected against pressure damages. • Cost reduction through substantially reduced air consumption. Longer service life. • Noise reduction for tools.
Water-resistant	No
Material seal	NBR
Additional information	Relieving at removal of supply pressure.

Dimensions

A mm	19
Connection A	G 1/4
B mm	59
SW mm	16
SW1 mm	19