

## 232A0430 ToolReg pressure regulator

ToolReg Regulator with relieving function, outlet pressure 3 bar, supply pressure max. 25 bar, female thread G 1/2, aluminium





### Product description

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 15 bar to 6 bar. With an outlet pressure tolerance of only  $\pm 10\%$  \*2 it is especially suitable for nailing machines.

Select the pressure regulator according to the desired outlet pressure. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

### More images



**Product properties**

|                               |                                                                                                                                                                                                                                                                                       |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Connection</b>             | Female thread G 1/2                                                                                                                                                                                                                                                                   |
| <b>Connection description</b> | Female thread G 1/2                                                                                                                                                                                                                                                                   |
| <b>Outlet pressure</b>        | 3 bar                                                                                                                                                                                                                                                                                 |
| <b>Seal description</b>       | Nitrite-butadiene rubber                                                                                                                                                                                                                                                              |
| <b>Flow rate in l/min</b>     | 1600                                                                                                                                                                                                                                                                                  |
| <b>Weight in kg</b>           | 0,075                                                                                                                                                                                                                                                                                 |
| <b>Hydraulics</b>             | No                                                                                                                                                                                                                                                                                    |
| <b>Material</b>               | Aluminium                                                                                                                                                                                                                                                                             |
| <b>max. inlet pressure</b>    | 25 bar                                                                                                                                                                                                                                                                                |
| <b>Medium suitability</b>     | compressed air or non-corrosive gases                                                                                                                                                                                                                                                 |
| <b>Surface</b>                | blank finish                                                                                                                                                                                                                                                                          |
| <b>Pneumatics</b>             | Yes                                                                                                                                                                                                                                                                                   |
| <b>Series</b>                 | 232                                                                                                                                                                                                                                                                                   |
| <b>Series long</b>            | 232                                                                                                                                                                                                                                                                                   |
| <b>Working temperature</b>    | 0°C up to +80°C                                                                                                                                                                                                                                                                       |
| <b>Advantages</b>             | <ul style="list-style-type: none"> <li>• Higher safety through lower pressure. Tools and equipment protected against pressure damages.</li> <li>• Cost reduction through substantially reduced air consumption. Longer service life.</li> <li>• Noise reduction for tools.</li> </ul> |
| <b>Water-resistant</b>        | No                                                                                                                                                                                                                                                                                    |
| <b>Material seal</b>          | NBR                                                                                                                                                                                                                                                                                   |
| <b>Additional information</b> | Relieving at removal of supply pressure.                                                                                                                                                                                                                                              |

**Dimensions**

|                     |       |
|---------------------|-------|
| <b>A mm</b>         | 30    |
| <b>Connection A</b> | G 1/2 |
| <b>B mm</b>         | 68    |
| <b>SW mm</b>        | 27    |
| <b>SW1 mm</b>       | 30    |