

## 232A0580 ToolReg pressure regulator

ToolReg Regulator with relieving function, outlet pressure 8 bar, supply pressure max. 25 bar, female thread G 3/4, aluminium





### Product description

In-Line pressure regulator with factory-set outlet pressure, reducing from e.g. 15 bar to 6 bar. With an outlet pressure tolerance of only  $\pm 10\%$  \*2 it is especially suitable for nailing machines.

Select the pressure regulator according to the desired outlet pressure. The outlet pressure cannot be subsequently adjusted. This safeguards against tampering.

### More images



#### Product properties

|                        |                                                                                                                                                                                                                                                                                       |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connection             | Female thread G 3/4                                                                                                                                                                                                                                                                   |
| Connection description | Female thread G 3/4                                                                                                                                                                                                                                                                   |
| Outlet pressure        | 8 bar                                                                                                                                                                                                                                                                                 |
| Seal description       | Nitrite-butadiene rubber                                                                                                                                                                                                                                                              |
| Flow rate in l/min     | 4600                                                                                                                                                                                                                                                                                  |
| Weight in kg           | 0,1                                                                                                                                                                                                                                                                                   |
| Hydraulics             | No                                                                                                                                                                                                                                                                                    |
| Material               | Aluminium                                                                                                                                                                                                                                                                             |
| max. inlet pressure    | 25 bar                                                                                                                                                                                                                                                                                |
| Medium suitability     | compressed air or non-corrosive gases                                                                                                                                                                                                                                                 |
| Surface                | blank finish                                                                                                                                                                                                                                                                          |
| Pneumatics             | Yes                                                                                                                                                                                                                                                                                   |
| Series                 | 232                                                                                                                                                                                                                                                                                   |
| Series long            | 232                                                                                                                                                                                                                                                                                   |
| Working temperature    | 0°C up to +80°C                                                                                                                                                                                                                                                                       |
| Advantages             | <ul style="list-style-type: none"> <li>• Higher safety through lower pressure. Tools and equipment protected against pressure damages.</li> <li>• Cost reduction through substantially reduced air consumption. Longer service life.</li> <li>• Noise reduction for tools.</li> </ul> |
| Water-resistant        | No                                                                                                                                                                                                                                                                                    |
| Material seal          | NBR                                                                                                                                                                                                                                                                                   |
| Additional information | Relieving at removal of supply pressure.                                                                                                                                                                                                                                              |

#### Dimensions

|              |       |
|--------------|-------|
| A mm         | 40    |
| Connection A | G 3/4 |
| B mm         | 102   |
| SW mm        | 34    |
| SW1 mm       | 40    |