

## 3118 04 10 Single banjo connection



LF 3000 standard pneumatic, Single Banjo, Engineered polymer, 4 mm - G 1/8"



### Product description

Connection of tubing at a 90° angle to a threaded port. Tightened on the top of the fitting with a flat spanner or socket wrench to facilitate assembly in tight spaces. The tube outlet can be orientated during assembly. - solid construction - full air flow, - individual unit quality control and dating in order to guarantee quality and traceability, - RoHS and ISO 14743.

### More images



**Product properties**

|                                        |                     |
|----------------------------------------|---------------------|
| <b>Weight in kg</b>                    | 0,012               |
| <b>Material</b>                        | Engineered polymer  |
| <b>Maximum working pressure in bar</b> | 20                  |
| <b>max. temperature in °C</b>          | 80                  |
| <b>min. temperature in °C</b>          | -20                 |
| <b>RoHS compliant</b>                  | Yes                 |
| <b>Vacuum resistance in mm Hg</b>      | 755                 |
| <b>Material seal</b>                   | NBR                 |
| <b>Material adjusting spindle</b>      | Brass nickel plated |
| <b>Material body</b>                   | Engineered polymer  |
| <b>Material toothed washer</b>         | Stainless steel     |

**Dimensions**

|           |        |
|-----------|--------|
| <b>C</b>  | G 1/8" |
| <b>E</b>  | 4      |
| <b>F</b>  | 13     |
| <b>G</b>  | 8,5    |
| <b>H</b>  | 17     |
| <b>L1</b> | 7      |
| <b>L2</b> | 18,5   |
| <b>ØD</b> | 4 mm   |