

## AG38-38AV Quick coupling



Quick coupling Single Shut-Off for male threads and shaped elements, 3/8" G, up to 400 bar, Aluminium



### Product description

- Quick connector for male threads and shaped elements
- Push-pull hand actuation
- Additional safety system against inadvertent disconnection
- Integrated shut-off valve
- Anodized aluminum
- Working pressure: from vacuum up to 50 bar (specifications for vacuum pressures on demand)

### More images



#### Product properties

|                                        |                                |
|----------------------------------------|--------------------------------|
| <b>Shut-off</b>                        | Quick coupling Single Shut-Off |
| <b>Connection description</b>          | for 3/8" male thread           |
| <b>Connection type</b>                 | for 3/8" male thread           |
| <b>Self-venting coupling</b>           | No                             |
| <b>Flat-sealing</b>                    | No                             |
| <b>Mould coupling</b>                  | No                             |
| <b>Weight in kg</b>                    | 0,2                            |
| <b>Hydraulics</b>                      | Yes                            |
| <b>Ball locking</b>                    | No                             |
| <b>Material</b>                        | Aluminium                      |
| <b>Maximum working pressure in bar</b> | 400                            |
| <b>Pneumatics</b>                      | Yes                            |
| <b>Safety locking system</b>           | Yes                            |
| <b>Standard product</b>                | Yes                            |
| <b>Pin lock</b>                        | No                             |
| <b>Vacuum suitable</b>                 | Yes                            |
| <b>Water-resistant</b>                 | Yes                            |
| <b>Two-hand operation</b>              | No                             |

#### Dimensions

|              |      |
|--------------|------|
| <b>A mm</b>  | 81   |
| <b>B mm</b>  | 38   |
| <b>CH mm</b> | 29   |
| <b>FA mm</b> | 3/8" |
| <b>FP mm</b> | 3/8" |
| <b>ØC mm</b> | 8,5  |
| <b>P mm</b>  | 10,5 |