

Logic element TIMER

Pneumatic delay, normally open (NO) or normally closed (NC), 4mm push-in connection




Product description

The Timer is part of Metal Work range of logic elements, which also includes OR, AND, NOT, YES, MEMORY. The value of the signal output delay is set by rotating a knob. It can work both as 3/2 NC and 3/2 NO, depending on whether feeding is through port "a" or port "b".

The maximum delay time can be increased by unscrewing a plug and connecting the port to an external auxiliary tank.

- Adaptor for 7 bar (DIN EN 50022) integrated in the body.
- Pressure indicator via an orange pin
- Pipe clamping system using Ø 4 built-in push-on fittings.

More images



Product properties

Connection	Push-in fitting 4 mm outside calibrated
Actuation	Pneumatic
Working pressure	2,5 – 8 bar
Flow rate in l/min	100 (at 6 bar)
Mounting position	In any position
Weight in kg	0,3
Medium suitability	Filtered, lubricated or unlubricated compressed air. If used, must be continuous.
Installation	An Omegaschiene (DIN EN 50022) Größe 35 x 7 oder 35 x 15 Wandmontage mit Löchern Ø 4.2
Resetting	spring operated
Material seal	NBR
Material spring	Spring steel
Material body	Anodized aluminium / Technopolymer

Dimensions