

## FM06LCF EO2-Functional nut for steel tubes

Tube outside diameter 6 mm, M 12×1,5, galvanized steel, NBR, light series



### Product description

Ermeto DIN fitting components for high pressure hydraulic tube fittings are indispensable items in order to build up a complete fitting series (EO-PSR, EO-2, EO2-FORM). The FM EO-2 functional nut is available with sealing NBR or sealing FKM.

Markets:

- Automotive
- Defense
- Energy
- Environment
- Industrial
- Infrastructure
- Machine Tools
- Materials Handling
- Mobile
- Oil and Gas
- Power Generation
- Process
- Transportation
- Water


Applications:

- Suitable for general hydraulic applications.

Features/ benefits:

- Steel and Stainless steel fittings have a high corrosion resistance to aggressive media and environmental influences.
- Depending on the specific requirements, the FM EO-2 functional nut can be delivered with sealing NBR or sealing FKM. This feature increase the range of applications.

### More images



## Product properties

|                                 |                     |
|---------------------------------|---------------------|
| Connection                      | M 12x1.5            |
| Series                          | Light               |
| Seal                            | NBR                 |
| Specifications met              | DIN ISO 8434        |
| Form                            | EO-2 functional nut |
| Material                        | Galvanized steel    |
| Maximum working pressure in bar | 500                 |
| Rohraußendurchmesser            | 6 mm                |
| Working temperature             | -40°C up to 250°C   |

## Dimensions

|     |          |
|-----|----------|
| L1  | 14,5     |
| ØD1 | 6        |
| S1  | 14       |
| T1  | M 12×1,5 |