

## M20SEODURX Nut

Tube outside diameter 20 mm, M 30×2,0, stainless steel, EO 24° cone end, heavy series



### Product description

Ermeto DIN fitting components for high pressure hydraulic tube fittings are indispensable items in order to build up a complete fitting series (EO-PSR, EO-2, EO2-FORM). The FM EO-2 functional nut is available with sealing NBR or sealing FKM.

#### Markets:

- Automotive
- Defense
- Energy
- Environment
- Industrial
- Infrastructure
- Machine Tools
- Materials Handling
- Mobile
- Oil and Gas
- Power Generation
- Process
- Transportation
- Water


#### Applications:

- Suitable for general hydraulic applications.

#### Features/ benefits:

- Steel and Stainless steel fittings have a high corrosion resistance to aggressive media and environmental influences.
- Depending on the specific requirements, the FM EO-2 functional nut can be delivered with sealing NBR or sealing FKM. This feature increase the range of applications.

### More images



## Product properties

|                                 |                     |
|---------------------------------|---------------------|
| Connection                      | M 30x2.0            |
| Series                          | Heavy               |
| Specifications met              | DIN ISO 8434        |
| Form                            | Nut EO 24° cone end |
| Material                        | Stainless steel     |
| Maximum working pressure in bar | 400                 |
| Rohraußendurchmesser            | 20 mm               |
| Working temperature             | -60°C up to 400°C   |

## Dimensions

|     |          |
|-----|----------|
| L4  | 24       |
| ØD1 | 20       |
| S1  | 36       |
| T1  | M 30×2,0 |