

GZ06L71 Swivel union

Tube outside diameter 6 mm, stainless steel, 24° DKO swivel, light series



Product description

Markets:


- Automotive
- Defence
- Energy
- Environment
- Industrial
- Infrastructure
- Machine Tools
- Materials Handling
- Mobile
- Oil and Gas
- Power Generation
- Process
- Transportation
- Water

Applications: Suitable for general hydraulic applications.

Features/ benefits:

- Steel and Stainless steel fittings have a high corrosion resistance to aggressive media and environmental influences. This attribute extends the life cycle of the fittings.
- Stainless steel surface: Ermeto DIN swivel-to-swivel high pressure hydraulic tube fittings , stainless steel version, have a high corrosion resistance to aggressive media and environmental influences, also a higher temperature resistance, than steel. These features extend the range of applications.
- High pressure: Ermeto DIN swivel-to-swivel high pressure hydraulic tube fittings have pressure ratings of up to 800 bar (S series) and 500 bar (L series), so that the fittings can be used in a wide range of applications.

More images



Product properties

Series	Light
Specifications met	DIN ISO 8434
Form	Swivel union
Material	Stainless steel
Maximum working pressure in bar	315
Connection tube outside diameter 1	6 mm
Connection tube outside diameter 2	6 mm
Working temperature	-60°C up to 400°C

Dimensions

Connection 1	24° DKO swivel
Connection 2	24° DKO swivel
L1	33
L2	33
ØD1	6
ØD3	2,5
S1	14
T	M 12×1,5