

## GZR22/18LCF Swivel reducer

Tube outside diameter 1 22 mm, Tube outside diameter 2 18 mm, galvanized steel, 24° DKO swivel, light series



### Product description

## Markets:


- Automotive
- Defence
- Energy
- Environment
- Industrial
- Infrastructure
- Machine Tools
- Materials Handling
- Mobile
- Oil and Gas
- Power Generation
- Process
- Transportation
- Water

Applications: Suitable for general hydraulic applications.

## Features/ benefits:

- Steel and Stainless steel fittings have a high corrosion resistance to aggressive media and environmental influences. This attribute extends the life cycle of the fittings.
- Stainless steel surface: Ermeto DIN swivel-to-swivel high pressure hydraulic tube fittings , stainless steel version, have a high corrosion resistance to aggressive media and environmental influences, also a higher temperature resistance, than steel. These features extend the range of applications.
- High pressure: Ermeto DIN swivel-to-swivel high pressure hydraulic tube fittings have pressure ratings of up to 800 bar (S series) and 500 bar (L series), so that the fittings can be used in a wide range of applications.

## More images



## Product properties

|                                           |                   |
|-------------------------------------------|-------------------|
| <b>Series</b>                             | Light             |
| <b>Specifications met</b>                 | DIN ISO 8434      |
| <b>Form</b>                               | Swivel reducer    |
| <b>Material</b>                           | Galvanized steel  |
| <b>Maximum working pressure in bar</b>    | 250               |
| <b>Connection tube outside diameter 1</b> | 22 mm             |
| <b>Connection tube outside diameter 2</b> | 18 mm             |
| <b>Working temperature</b>                | -40°C up to 250°C |

## Dimensions

|                     |                |
|---------------------|----------------|
| <b>Connection 1</b> | 24° DKO swivel |
| <b>Connection 2</b> | 24° DKO swivel |
| <b>L1</b>           | 42             |
| <b>L2</b>           | 44             |
| <b>ØD1</b>          | 22             |
| <b>ØD2</b>          | 18             |
| <b>ØD3</b>          | 13             |
| <b>S1</b>           | 36             |
| <b>S2</b>           | 32             |
| <b>T1</b>           | M 30×2,0       |
| <b>T2</b>           | M 26×1,5       |