

25SDTF08MPN Plug with hose barb





Plug safety double shut-off, hose barb 8mm (5/16), nominal diameter 7,4, <35 bar, brass nickel plated, seal NBR



Product description

35 bar (Brass-Version) 70 bar (with steel body and steel sleeve) maximum static working pressure with safety factor 4 to 1.

More images



Product properties

Shut-off	Plug Safety (double shut-off)
Connection	Hose barb 8mm LW(5/16")
Connection description	Hose barb 8mm LW(5/16")
Connection type	Hose barb
Suitable breath / respiratory protection	Yes
Seal	NBR
Seal description	Nitrite-butadiene rubber
Working pressure	35 bar maximum static working pressure with safety factor 4 to 1.
Pressure eliminator	No
Single-hand operation	No
Self-venting coupling	No
Flat-sealing	No
Mould coupling	No
Weight in kg	0,047
Hydraulics	No
Compatibility	RECTUS 26 RECTUS 1600/1625 TEMA 1600
Ball locking	No
Material	Brass nickel plated
Material description	Brass CuZn39Pb3 2.0401 (except sleeve)
Bore area in mm²	43
Bore in mm	7,4
Surface	nickel plated
Pneumatics	Yes
Professional recommendation	Breathing protection
Series	25
Series long	25SD
Safety locking system	Yes
Standard product	No
Pin lock	No
Working temperature	-20°C up to +100°C (NBR) -40°C up to +120/150°C (EPDM) -15°C up to +200°C (FKM) 0°C up to +316°C (FFKM) depending on the medium.
Ultra-FLO-valve	No
Vacuum suitable	No
Advantages	Handy sleeve for optimum operation even with gloves.
Water-resistant	Yes
Material connection	Brass nickel plated
Material seal	Perbunan®
Material spring snap ring	stainless steel AISI 301
Material valve	Brass
Two-hand operation	Yes

Dimensions

Connection A	8 mm
L mm	60
L1 mm	25
SW mm	21